

IP 2912 is a semi-rigid, clear PET that should be utilised where a clear film with excellent print characteristics is required for all kinds of display applications. It should be reverse-printed on the front side of the product, allowing for display applications with high levels of transparency. It can also be laminated with a product such as IP 2503 (white opaque), IP 2516 (white translucent) or a mirror film (such as 3M Series 7755) to create a high-impact product for display applications. It is suitable for conversion with eco-solvent and solvent inks, as well as UV-cured inks.

IP 2912

IP 2912 is a semi-rigid, PET that should be utilised where a clear film is required for indoor and outdoor (short term) display applications. It affords high levels of water resistance and abrasion resistance and excellent print characteristics. Albeit a semi-rigid product, it is very flexible. It is suitable for conversion with eco-solvent and solvent inks, as well as UV-cured inks. In the event that there are loading issues with this product, the printer sensors can be easily bypassed by applying a 15cm strip of application tape across the width of the roll. Laminate: compatible with all IP laminate options.

Specifications	
DESCRIPTION	Semi-Rigid Clear PET
COLOUR	Clear Gloss
THICKNESS	200 μ
WEIGHT	280g / m ²
ADHESIVE	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	-15°C to +70°C
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2009 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.