

Frontlit Banner Gloss is a premium coated banner material with excellent thermal welding characteristics. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2110 Plus

IP 2110 Plus is a flexible and soft top-quality banner material. It can be used for indoor and outdoor applications such as billboards at trade shows and events, construction sites, show rooms, promotional campaigns and many other applications. This material has been UV-stabilized and features an anti-fungus treatment. Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	Frontlit banner
COLOUR	White gloss
FACE FILM THICKNESS	460μ
WEIGHT	550g / m <sup>2</sup>
ADHESIVE	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	-20°C to +70°C
DURABILITY (UNPRINTED)	Up to 5 years
FLAME RETARDANCY	N/A
TOP COAT	Acrylic
TENSILE STRENGTH	2300 / 2200 (N / 5cm)      DIN 53354
TEAR RESISTANCE	220 / 220 (N)      DIN 53386
SHELF LIFE	1 year, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© May 2008 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.