

White gloss polymeric vinyl with a permanent solvent-based adhesive. This material, which is a milestone in terms of ImagePerfect printable polymeric vinyls, has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2503 Plus

In relation to the 'classic' IP 2503 product, this re-engineered version manifests itself as a quantum leap in terms of the quality of the printed output. The new film features specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure long-term outdoor durability, and the product as a whole benefits from an aesthetic face-lift via the incorporation of a super-white liner (which also allows for increased layflat). IP 2503 Plus is a state-of-the-art product that will allow for the creation of unbeatable printed output for indoor and outdoor applications such as markings & decorations and vehicle graphics. It also incorporates a B1 fire rating. Laminate: IP 2810-101, IP 2810-200 or ImagePerfect™ water-based liquid laminate with UV protection.

| Specifications         |  |
|------------------------|--|
| DESCRIPTION            | Polymeric vinyl  |
| COLOUR                 | White gloss  |
| FACE FILM THICKNESS    | 70μ  |
| WEIGHT                 | N/A  |
| ADHESIVE               | Solvent acrylic permanent  |
| ADHESIVE STRENGTH      | 20N / 25mm (Finat TM 1/24h)  |
| RELEASE PAPER          | PE-coated silicone paper, 140g / m <sup>2</sup>  |
| TEMPERATURE RANGE      | -30°C to +90°C   |
| DURABILITY (UNPRINTED) | Up to 7 years  |
| FLAME RETARDANCY       | B1   |
| SHELF LIFE             | 2 years, 20°C / 50% humidity   |
| RECOMMENDATION         | For optimum quality, please ensure that the media feed adjustment has been completed for this material |

© October 2009 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.