

IP Mounting Tape is a highly cohesive tape designed for seaming and splicing of paper-based banners and media as well as a broad range of synthetic media made of PP, PET and Tyvek.

## IP Mounting Tape

Featuring a very strong initial and durable adhesive strength, this double sided adhesive tape is essential for all kinds of applications. It works well on many low-energy surfaces, too. Ideal for P.O.S., pop-up & roll-up displays, many synthetic materials, carton, paper and many closed-mesh and coated textiles. IP Mounting Tape is not resistant to plasticizers. A clean substrate and high contact pressure using a film roller are indispensable for successful application. IP Mounting Tape should be applied at room temperature 24 hours prior to mounting the assembly.

| Specifications    |                             |
|-------------------|-----------------------------|
| DESCRIPTION       | D/S transfer tape           |
| COLOUR            | Transparent                 |
| THICKNESS         | 100 $\mu$                   |
| WEIGHT            | N/A                         |
| ADHESIVE          | Rubber based                |
| ADHESIVE STRENGTH | 23N / 25mm (Finat TM 1/24h) |
| RELEASE PAPER     | Silicone paper, brown       |
| TEMPERATURE RANGE | -20°C to +70°C              |
| DURABILITY        | N/A                         |
| FLAME RETARDANCY  | N/A                         |
| SHELF LIFE        | 1 year, 20°C / 50% humidity |

© January 2007 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.